

[54] **CORNER FINISHING TOOL**

[75] Inventors: **Eugene R. Johnson**, Burlingame;  
**Morris F. Mower**, Santa Clara, both  
of Calif.

[73] Assignee: **Bliss & Laughlin Industries, Inc.**,  
Oak Brook, Ill.

[22] Filed: **Sept. 9, 1974**

[21] Appl. No.: **504,253**

[52] U.S. Cl. .... **425/458; 15/235.7; 425/87**

[51] Int. Cl.<sup>2</sup> ..... **B28B 7/08; B05C 17/10**

[58] Field of Search ..... **425/87, 458; 15/235.3,**  
**15/235.4, 235.5, 235.6, 235.7, 235.8, 236 R;**  
**401/9; 52/749**

[56] **References Cited**  
**UNITED STATES PATENTS**

2,178,899	11/1939	Shaffer.....	15/235.7
2,594,606	4/1952	Ames.....	425/87
2,595,742	5/1952	Wood.....	15/235.7

2,608,853	9/1952	Schrepper.....	15/235.7
2,787,056	4/1957	Dobratz.....	15/236 R X
3,237,235	3/1966	Moody.....	15/235.3

*Primary Examiner*—Francis S. Husar

*Assistant Examiner*—John S. Brown

[57] **ABSTRACT**

A corner finishing tool for applying mastic material along a wall joint comprising an angular retainer plate having a pair of integral sides resiliently joined at a corner, a pair of L-shaped rigid frame members secured thereto, one side and frame member being resiliently movable relative to the other side and frame member while together defining a cavity reservoir for mastic material, and a wheel having substantially conical side surfaces that converge to a center rim. The corner finishing tool also provides means for setting the L-shaped rigid frame members to a preset position under an adjustable resilient biasing force.

**9 Claims, 7 Drawing Figures**

